

ADDRESS :

SUNFIELD INC
 Ladson Business Center
 3525 Iron Horse Drive,
 Unit# 106
 LADSON SC 29456 (USA)

**MAILING ADDRESS :**

SUNFIELD INC.
 P O BOX 1139
 LADSON SC 29456

Awning Marine Technical Features

Composition	100% Solution Dyed Woven Acrylic	Mildew Resistant	Yes. (Test: AATCC30)
Warp	76 ends/inch. Yarn count: 20/2	Abrasion Resistant	Yes> 20000 cycles (Test: ASTM D 1966)
Fill	38 ends/inch. Yarn count: 20/2	Finished Widths	32", 47", & 60"
Finished Weight	305 g/sq.m (9.0 Oz/Sq. yard)	Standard Put Up	65 yds per roll.
Tensile Strength (grab)	Warp: 295 Lbs, Fill: 175 LBS (Test: ASTM S 5034)	Heat Sealable	Yes with a seam tape.
Tear Strength (Tongue)	Warp: 13.8 Lbs, Fill: 9.4 Lbs (Test: ASTM D 2261)	Breathable	Yes
Water Column	>300mm (>12") (Test: UNI 5122)	Translucent	Yes
Water Repellent	Yes (Test: AATCC 127-1985)	Opaque	Yes
Wetting-No. Droplet saturation.	100. (Test: AATCC-22-1996)	Heat Transfer Films	Yes
Stain Repellent	Yes Protective Fluorocarbon finish.	Heat Sealed insert Fabric	Yes
Stretch Factor	Warp: 0.3%, Fill: 0.3% (Test: ASTM D 3107)	Sewn-in insert Fabric	Yes
UV Resistant	Yes: 1500+Hours (Xenon Weather meter)	Pressure Sensitive Vinyl	Yes
UV Protection	Rated: Excellent (Test: AS/NZS 4399:1996)	Silk Screening	Yes
Color Fade Resistant	Yes 7/8 -8 degree solution dyed colors (UNI 7640)	Hand Painting	Yes
Warranty	Yes 10 Years*	Uses	Awnings, Boat Covers, Banners etc.

***The warranty is effective only if the fabric has been unserviceable because of loss of color or strength from normal exposure conditions including sunlight and atmospheric chemicals. The warranty does not apply against deterioration of any kind due to fire accidents, burns, abusive use, malfunction, negligence, vandalism, perforations, or other acts of God. The warranty does not cover any labor or installations.**

PHONE :

+1- 866- 828- 7326
 +1- 843 - 408-4852

FAX :

+1- 843- 879-9236

E-MAIL :info@sunfieldusa.com