

ADDRESS :

SUNFIELD INC
 Ladson Business Center
 3525 Iron Horse Drive,
 Unit# 106
 LADSON SC 29456 (USA)

**MAILING ADDRESS :**

SUNFIELD INC.
 P O BOX 1139
 LADSON SC 29456

Furniture Technical Features

Composition	100% Solution Dyed Woven Acrylic	Finished Widths	54"
Warp	72 ends./inch Yarn Count:20/2 (Test: UNI 8099/80)	Standard Roll Put Up	65 yds. Per roll
Fill	32 ends/inch Yarn Count:20/2 (Test: UNI 8099/80)	Heat Sealable	Yes. With seam tape.
Finished Weight	Approx. 8 Oz/Sq Yard (270 g/sq.m)	Water Repellent	Yes (Test: AATCC 127-1985)
Tensile Strength (grab)	Warp: 331 lbs., Fill: 121 lbs. (Test: ASTM D 5034)	Breathable	Yes
Tear Strength (tongue)	Warp: 19.1 lbs., Fill: 15.45 lbs. (Test: ASTM D 2261)	Translucent	Yes
Water Column	>8.8" (>22cm) (Test: AATCC127-Option 1)	Opaque	Yes
Mildew Resistant	Yes (Test AATCC 30)	Heat Transfer Film	Yes
Stain Repellent	Yes. Protective Fluorocarbon finish.	Heat Sealed Insert Fabric	Yes
UV Resistant	Yes: 1500+ Hours(Xenon Weather-Ometer)	Sewn-in Insert Fabric	Yes
UV Protection	Excellent(Test; AS/NZS 4399)	Pressure Sensitive Vinyl	Yes
Color Fade Resistant	7/8-8 degree solution dyed colors (UNI EN ISO 105-B04)	Silk Screening	Yes
Abrasion Resistant	(Wyzenbeek 900 cycles) Rating: Light duty (ASTM D3597)	Hand Painting	Yes
Stretch Factor	Warp 0.3%, Fill: 0.3% (Test: ASTM D 3107)	Uses	Cushions, Furniture, etc.
Wetting-No Droplet Saturation	100. (Test: AATCC-221996)	Warranty	Yes, 3 years*
Flammability:			
1. Passes the requirements of California 117 Section E.			
2. Passes the requirements of UFAC- Fabric, Class-1.			

PHONE :

+1- 866- 828- 7326
 +1- 843 - 408-4852

FAX :

+1- 843- 879-9236

E-MAIL : info@sunfieldusa.com